

PPG Colour Collection



Choosing paint colours can be tricky. That's why at Leyland Trade we've done the hard work for you. The Leyland Trade Colour Card includes a compact range of our best selling colours, ideal for both homes and businesses.



Harbour Light | Vinyl Matt



Steel Mill | Hardwearing Matt



Dove Grey | Smooth Masonry

American Anthem | Hardwearing Acrylic Eggshell

British Standards BS4800 Colour Range

Undercoat Key	
UC01 White	UC50 Deep Cream
UC44 Pearl	UC52 Mid Grey
UC45 Bright Orange	UC53 Dark Grey
UC46 Mid Blue	UC56 Ochre
UC47 Tan	UC57 Cream
UC48 Slate	UC62 Red
UC49 Light Green	UC63 Dark Red
LRV Light Reflectance Value (see back cover for more information)	

Heavy Duty Floor Paint

The Leyland Truguard range of exterior finishes provides a collection of high quality, long-lasting and protective coatings. In addition to the thousands of tinted colours available, the Truguard masonry range also includes this classic collection of ready mixed colours in a variety of high quality finishes.

--	--	--	--

--	--	--	--

--	--





Product & Colour Guide

Leyland Trade

Light Reflectance Value (LRV)
LRV is a measurement that tells you how much light a colour reflects. Visual contrast is achieved by differences in LRV. To meet the requirements of the The Equalities Act, the Building Regulations Part M recommends a minimum of 30 points between colours on adjacent critical surfaces (e.g. floors/walls). A wall colour with a higher LRV can also support sustainable lighting plans by helping to propagate daylight into a space and reduce the amount of lighting required.

Health & Safety The Health and Safety at Work Act 1974 places a responsibility upon manufacturers and suppliers of substances for use at work to ensure, so far as is reasonably practical, that they will be without risk to health when properly used. Suppliers are also required to provide users with information on the nature of any hazards of the materials supplied, together with recommended precautions for their safe use. Please refer to the Health and Safety Data Sheets.

Waste & Product Disposal Purchase only the correct amount for the job to be carried out by using the coverage rate given on the product container. Scrape as much product as possible from equipment before cleaning. Use only the minimum amount of cleanser and re-use as often as possible. Ensure container is re-sealed fully after use. Store in a cool, dry, frost free place. Contact your local authority regarding disposal of washings and waste paint. Do not empty product into drains or watercourses.

Lead in Previously Painted Surfaces Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Further Information We have produced the colour shown on this colour card as accurately as printing will allow. Please ensure you use a tester Pot before decorating as a colour can appear very different depending on the lighting available and the room and surface where it is being used.

Your local Leyland Trade stockist

www.leylandtrade.com /LeylandTrade
Enquiries: +44 (0)1924 354354 /LeylandTrade
Email: customersupport.acuk@ppg.com

Leyland Trade

About us

Leyland Trade offer a core range of quality, affordable trade paints that you can rely on for a job well done. This expertise is built through our longstanding heritage - we've been making paint since 1922.

Product features key

- Apply with roller
- Apply with brush
- Apply with spray
- Apply with trowel
- Suitable for interior use
- Suitable for exterior use
- Suitable for interior & exterior use
- Available to tint

Product features



WATER BASED

Water based paints in this booklet have minimal/very low VOCs (Volatile Organic Compound) and are easily recognised by their very low odour and quick drying properties.

Water based paints are sometimes referred to by customers as:

- Acrylic paints
- Quick drying paint
- Low odour paints



SOLVENT BASED

Solvent based paints in this booklet have high/very high VOCs which are released into the atmosphere as the paint dries. Solvent based paints are easy to apply, tough and durable.

Solvent based paints are sometimes referred to by customers as:

- Alkyl based
- Traditional paint
- Oil based
- Spirit based

Walls & ceilings

	PACK SIZE	COVERAGE	RECOAT TIME	APPLICATION	INTERIOR/ EXTERIOR	VOC CONTENT
Smart Matt • No brush or roller marks • Quick and easy touch up when applied to damaged areas • Professional result with every application		10/2.5	12 METRES APPROX	4 HRS		LOW
Smart Multi-Surface • Suitable for use on walls, ceilings, wood and metal • Moisture resistant - suitable for all rooms • Tough and durable satin finish		7.5/2.5	12 METRES APPROX	3-4 HRS		LOW
Hardwearing Acrylic Eggshell • Suitable for kitchens, bathrooms and busy areas • Superior durability • Stain and moisture resistant		10/2.5	12 METRES APPROX	3-4 HRS		
Hardwearing Matt • Suitable for kitchens, bathrooms and busy areas • 10 times tougher than Vinyl Matt • Stain and moisture resistant		10/2.5	12 METRES APPROX	4 HRS		
Vinyl Matt • Wipeable finish • Excellent covering power • Hides imperfections		10/2.5	14 METRES APPROX	2-4 HRS		
Vinyl Silk • Washable finish • Easy to apply • Easy to clean		10/2.5	12 METRES APPROX	3-4 HRS		
Vinyl Soft Sheen • Washable finish • Easy to apply • Easy to clean		2.5/5	12.5 METRES APPROX	3-4 HRS		
Super Leytex Matt • Breathable - suitable for new plaster • Excellent covering power		15/10	13 METRES APPROX	2-4 HRS		
Contract Matt • Ideal for most large jobs and new builds • Good covering power		10/15	13 METRES APPROX	2-4 HRS		
Contract Silk • Ideal for most large jobs and new builds • Wipeable finish		10	12 METRES APPROX	3-4 HRS		
Alkali Resisting Wall Primer • Masks stains and smells • Excellent adhesion • Suitable for interior and exterior masonry surfaces and fibreglass		2.5/5	10 METRES APPROX	16-24 HRS		HIGH
Anti-Damp Paint • Resists blistering • Mid-sheen finish • Suitable for all types of wall surfaces		2.5/5	10 METRES APPROX	6 HRS		LOW
Damp Block • Provides a water resistant barrier • Masks damp spots and water marks • Suitable for overcoating with wallpaper or any emulsion paint		7.5/2.5	8 METRES APPROX	12 HRS		LOW
Stain Blocking Primer • Prevents stains from reappearing • Locks in stains		2.5	8 METRES APPROX	2-4 HRS		VERY HIGH
Direct to Metal Paint • Hardwearing protection • Smooth, semi-gloss finish • Suitable for bare, previously painted or weathered metal surfaces		7.5/2.5	10 METRES APPROX	2-4 HRS		HIGH
Anti-Corrosive Metal Primer • Inhibits rust • Suitable for all metal surfaces • Overcoat with any Leyland trim product		2.5	11 METRES APPROX	14-16 HRS		HIGH
MDF Primer • Suitable for use on interior and exterior, medium density fibre board • Low odour • Quick drying		7.5/2.5	13 METRES APPROX	1-2 HRS		LOW
Anti-Slip Floor Paint • Textured, semi-gloss finish • Suitable for concrete, steel and wooden floors • Slip resisting		5	11 METRES APPROX	16-24 HRS		VERY HIGH
Heavy Duty Floor Paint (Colours) • Tough and durable - resistant to mild chemicals • Protective satin finish • Suitable for concrete and wood floors		2.5/5	11 METRES APPROX	16-24 HRS		HIGH
Heavy Duty Floor Paint (Clear) • Tough and durable - resistant to mild chemicals • Protective satin finish • Suitable for concrete and wood floors		2.5/5	17 METRES APPROX	24 HRS		HIGH

Specialist coatings

	PACK SIZE	COVERAGE	RECOAT TIME	APPLICATION	INTERIOR/ EXTERIOR	VOC CONTENT
High Gloss • High quality gloss finish • Tough and durable • Excellent flow and levelling properties to allow easy application		10/2.5	17 METRES APPROX	16-24 HRS		HIGH
One Coat Gloss • Quick application • Excellent covering power • Self-undercoating		7.5/2.5	10 METRES APPROX	16-24 HRS		HIGH
Non-Drip Gloss • Drip resistant • Self-undercoating • Easy to apply		7.5/2.5	14 METRES APPROX	16-24 HRS		HIGH
Satinwood • High quality satin finish • Tough and durable • Self-undercoating		7.5/2.5	20 METRES APPROX	16-24 HRS		HIGH
Eggshell • A high quality mid-sheen finish • Tough and durable • Washable finish		5/2.5	20 METRES APPROX	16-24 HRS		HIGH
Undercoat • Ideal base coat for gloss • Great covering power • Provides adhesion		5/2.5	17 METRES APPROX	16-24 HRS		HIGH
Acrylic Primer Undercoat • Suitable for interior and exterior wood, plaster, drywall and render • A general purpose, water-based undercoat • Quick drying with low odour		5/2.5	13 METRES APPROX	1-2 HRS		MEDIUM
Wood Primer • Suitable for interior and exterior bare timber • Excellent adhesion • Smooths uneven surfaces		5/2.5	12 METRES APPROX	16-24 HRS		HIGH
All Purpose Primer • Suitable for interior and exterior wood, metal, plaster and masonry • Anti-corrosive properties • Provides adhesion		7.5/2.5	12 METRES APPROX	16-24 HRS		HIGH
Fast Drying Gloss • Non-yellowing and low odour • Excellent flow and levelling properties • Suitable for interior and exterior wood and metal		7.5/2.5	15 METRES APPROX	3-4 HRS		MEDIUM
Fast Drying Satin • Non-yellowing and low odour • Excellent flow and levelling properties • Suitable for interior and exterior wood and metal		7.5/2.5	15 METRES APPROX	3-4 HRS		LOW
Fast Drying Undercoat • Provides excellent adhesion • High opacity and low odour • Suitable for interior and exterior wood and metal		7.5/2.5	13 METRES APPROX	1-2 HRS		LOW
Smooth Masonry • Protects against weathering for up to 15 years • Suitable for all masonry surfaces • Anti-carbonation properties		5/10	10 METRES APPROX	4-6 HRS		LOW
Pliolite Based Masonry • Can be applied in temperatures as low as -5°C • Resistant to rain within 20 minutes of application • Smooth, robust matt finish		5	8 METRES APPROX	24 HRS		HIGH
Hi-Textured Masonry • Up to 10 years protection • Suitable for all masonry surfaces • Robust and durable		10	1 METRES APPROX	48-72 HRS		MEDIUM
Fine Textured Masonry • Protects against weathering for up to 10 years • Suitable for all masonry surfaces • Anti-carbonation properties		5	8 METRES APPROX	4-6 HRS		LOW
Stabilising Masonry Primer • A clear solution for binding friable, chalky masonry surfaces • Use with Truguard masonry coatings • Highly penetrative		2.5/5	6 METRES APPROX	16-24 HRS		VERY HIGH
Flexible Exterior Gloss • Flexible, durable and water-resisting gloss finish • Outperforms conventional gloss by up to 2 years • Use with Truguard Flexible Exterior Undercoat		7.5/2.5	15 METRES APPROX	16-24 HRS		HIGH
Flexible Exterior Undercoat • Suitable for timber and metal • Use with Truguard Flexible Exterior Gloss		7.5/2.5	12 METRES APPROX	16-24 HRS		HIGH

Interior trim & primers

Exterior masonry & wood

Technical Support is available

We have an experienced team who are here to help! They're dedicated to providing you with a high quality, effective service and back up support. So that at every step of the way and whilst building relationships with your customers and clients, we'll help you to differentiate your business.

Our extensive package of technical support services are just a phone call away. We're here to guide you through key issues that affect the selection and application of all of our surface coatings.

Find out more about Leyland Trade product options by calling us today on:

01924 354 354